

NLC3P

L-3



IMPROVED RESISTANCE TO AGGRESSION IN HARD LOADING CONDITIONS

- 35.5mm tread depth, which is 6% higher over regular L-3 patterns
Benefit: Extended wear life, improved cut resistance.
- Heavy casing and solid centerline section
Benefit: To resist rip and tear in extreme working conditions.
- Wide and open lug tread
Benefit: To provide optimal ground contact, greater stability and self-cleaning capability.



| Size | Ply Rating | TRA Code | Rim | Dimension | | Load Capacity | | Inflation Pressure | | Tread Depth (mm) | Type |
|---------|------------|----------|-----------|--------------------|-----------------------|---------------|--------|--------------------|--------|------------------|------|
| | | | | Section width (mm) | Overall diameter (mm) | 10km/h | 50km/h | 10km/h | 50km/h | | |
| 23.5-25 | 16 | L-3C | 19.50/2.5 | 595 | 1615 | 9500 | 6150 | 300 | 225 | 35.5 | TT |
| 23.5-25 | 20 | L-3C | 19.50/2.5 | 595 | 1615 | 10900 | 7300 | 375 | 300 | 35.5 | TT |
| 23.5-25 | 24 | L-3C | 19.50/2.5 | 595 | 1615 | 12500 | 8000 | 475 | 350 | 35.5 | TT |