



## **UTL3 Bulldozer Tires**

The UTECH UTL3 is a loader and dozer tire pattern that is designed for long lasting performance in traction, stability, cut and impact resistance. It also offers low operational costs and excellent operator comfort safety.



### **Parts Details Of UTL3 Bulldozer Tires**

#### **Special sidewall design and thickened sidewall for better cut and puncture resistance:**

- A special shoulder design applied to protect the sidewall from rocks and debris, and the sidewall is thickened to minimize damages from cuts.
- Super thick tread base is applied to increase the puncture resistance.



## Non-directional, multi-block tread engineered for superior traction and stability

- The non-directional tread design with big blocks and open shoulder grooves delivers high fore, aft and lateral traction, and superior self-cleaning capability
- The ultra-wide tread design and enhanced radial construction design offer improved stability and high flotation.

## More rubber to be worn and less heat generated:

- UTL3 is designed with 10% more rubber volume compared with competitors and wear resistant rubber compound is used to increase the wear life.
- Tread movement is limited so as to decrease the heat generation.

## Improved impact resistance and extra load capacity enabled by reinforced tire architecture:

- The high tensile steel belt package built in for better impact and puncture resistance, and robust carcass is designed to deal with frequent twisting in application.

## Specifications of UTL3 Bulldozer Tires

Size	Star Rating	TRA Code	Rim	Section width		Overall Diameter		Tread Depth		Load Index & Speed Symbol	Type
				in	mm	in	mm	32nds	mm		
17.5R25	★★	E3/L3	14.00/1.5	17.52	445	53.07	1348	35	28	167B/182A2	TL
20.5R25	★★	E3/L3	17.00/2.0	20.47	520	58.74	1492	35	28	177B/193A2	TL
23.5R25	★★	E3/L3	19.50/2.5	23.5	597	63.66	1617	40	31.5	185B/201A2	TL



## Duratech Industrial (Jinan) Co., Ltd

---

26.5R25	★★	E3/L3	22.00/3.0	26.5	673	68.9	1750	45	36	193B/209A2	TL
29.5R25	★★	E3/L3	25.00/3.5	29.53	750	73.74	1873	54	43	200B/216A2	TL
29.5R29	★★	E3/L3	25.00/3.5	29.53	750	77.76	1975	54	43	202B/218A2	TL